

SEE OUR FULL LINE OF PRODUCTS AT: **PELICAN.COM**



PELICAN LIGHTING TOOLS

- Safety Approved lights for hazardous locations
- Specialized lights for fire and rescue operations
- Headlights
- Submersible lights for diving
- Law Enforcement



PELICAN REMOTE AREA LIGHTS

- Solid-state mounted LEDs
- Portable
- Multi-directional lamp heads
- Up to 15 hours of burn time
- Rechargeable



PELICAN PROTECTOR CASES

- Watertight, dustproof, crushproof
- Micro Cases for small electronics
- Specialized laptop and tool organization solutions for off site jobs
- Ruggedized shipping cases for transporting oversize items

INJECTION MOLDED CASES

Pelican Products, Inc. guarantees its products for a lifetime against breakage or defects in workmanship. Pelican™ injection molded cases are guaranteed to be watertight to a depth of 3.3 feet (1 meter) for 30 minutes (IP 67) if properly closed with undamaged o-ring in place unless otherwise stated. Pelican's liability is limited to the case and not its contents or foam. All warranty claims of any nature are barred if the container has been altered, damaged or in any way physically changed, or subjected to abuse, misuse, negligence or accident. Refer to www.pelican.com/warranty for full details.

ROTO MOLDED AND SPECIALTY CASES

Pelican guarantees its Roto Molded cases for 1 year against defects in materials and workmanship and 90 days on hardware from the proof of purchase. All warranty claims of any nature are barred if the container has been altered, damaged or in any way physically changed, or subjected to abuse, misuse, negligence or accident. Refer to www.pelican.com/warranty for full details.

FLASHLIGHTS

Pelican Products, Inc. guarantees its flashlight products for a lifetime against breakage or defects in workmanship. This guarantee does not cover the lamp or batteries (rechargeable or disposable). All warranty claims of any nature are barred if the flashlight has been altered, damaged or in any way physically changed, or subjected to abuse, misuse, negligence or accident. Refer to www.pelican.com/warranty for full details.

RALS (Remote Area Lighting Systems) Products

Pelican guarantees its RALS products for 1 year against defects in materials and workmanship from the date of purchase. All warranty claims of any nature are barred if the product has been altered, damaged or in any way physically changed, or subjected to abuse, misuse, negligence or accident. Refer to www.pelican.com/warranty for full details.

Refer to www.pelican.com/warranty for full details of Pelican warranties.



23215 Early Avenue, Torrance, CA 90505
Tel: 310.326.4700 • 800.473.5422 • Fax: 310.326.3311
www.pelican.com

Part No. 0030-008-200 SP/13

© 2011 Pelican Products, Inc.
All trademarks are registered and/or unregistered trademarks of Pelican Products, Inc., its subsidiaries and/or affiliates. iPad is a registered trademark of the Apple Inc.

DISTRIBUTED BY:

PELICAN™



REMOTE AREA LIGHTING

LED HEADLIGHTS

PROTECTOR CASES

FLASHLIGHTS

SELECTED PRODUCTS FOR THE RAIL INDUSTRY

For more info, visit www.pelican.com



PELICAN™

REMOTE AREA LIGHTING SYSTEMS

HEADLIGHTS

FLASHLIGHTS

CASES



MANY MORE FLASHLIGHT MODELS TO CHOOSE FROM

PROTECTOR CASE™ APPLICATIONS

350
CASE
SIZES

- Spare part containment equipment
- Track calibration equipment gear
- Laptop computers, iPad®, and Netbooks
- First aid and rescue equipment
- Relay repair kits
- Small hand and power tools
- Signal parts
- Routine diagnostic inspection equipment



Photography: Caltrans Highway Repair Crew (A, B), Rail Worker (C).

Pelican builds lighting tools and cases for use in the most extreme environments. The unique rechargeable Remote Area Lighting Systems illuminate larger work areas and are portable, quiet, clean and safe. Our headlights use the latest in LED technology. You can rely on our handheld lights for durability and ease of use. Transport your tools and other instruments in a Pelican case to ensure they will arrive fully operational.

SPECIFICATIONS

RALS	BATTERIES Included	WEIGHT with Batteries	LENGTH Extended Height	LUMENS	RUNTIME	BEAM SPREAD	LEDs	HEADS	APPROVALS
9420	Lithium Ion	8.4 lbs. (3.81 kg)	62" (157.4 cm)	1000 (high) 500 (low)	2h (high), 4h (low)	58°	2 per head	1	N/A
9430	12v Rechargeable, Sealed	22.05 lbs. (10 kg)	32.28" (82 cm)	2000 (high) 1000 (low)	8h (high), 15h (low)	90°	24 per head	1	N/A
9430SL	12v Rechargeable, Sealed	22.05 lbs. (10 kg)	32.28" (82 cm)	2000 (high) 1000 (low)	8h (high), 15h (low)	10°	24 per head	1	N/A
9435	Rechargeable NiMH	17.6 lbs. (7.98 kg)	32.28" (82 cm)	1500 (high) 750 (low)	5h (high), 10h (low)	90°	18 per head	1	CI D2
9460RS	12v Rechargeable, Sealed	50.71 lbs. (23 kg)	70.87" (179.9 cm)	4000 (high) 2000 (low)	7h (high), 14h (low)	90°	24 per head	2	N/A
9470RS	12v Rechargeable, Sealed	88.18 lbs. (40 kg)	72.85" (185 cm)	8000 (high) 4000 (low)	7h (high), 14h (low)	90°	24 per head	4	N/A
9440	Rechargeable NiMH	16.09 lbs. (7.3 kg)	86.25" (219 cm)	2400 (high) 1200 (low)	3h (high), 6h (low)	120°	10 per head	1	N/A

HEAD LIGHTS	BATTERIES * Batteries Included	WEIGHT with Batteries	LENGTH	ANSI LIGHT OUTPUT	ANSI RUNTIME	APPROVALS
2690 LED	3 AAA Alkaline*	4.1 oz. (0.12 kg)	2.81" (7.1 cm)	60	10h 30m	CI II III D1
2720 LED	3 AAA Alkaline*	3.8 oz. (0.11 kg)	2.81" (7.1 cm)	80 (high) 5 (low)	8h (high), 175h (low)	N/A
2740	3 AAA Alkaline*	3.3 oz. (0.09 kg)	2.25" (5.7 cm)	35 (high) 13 (low)	20 (high), 51h (low)	N/A
2750	3 AAA Alkaline*	3.4 oz. (0.1 kg)	2.25" (5.7 cm)	100 (high) 40 (low)	3h 45m (high), 12h (low)	N/A

FLASHLIGHTS	BATTERIES * Batteries Included	WEIGHT with Batteries	LENGTH	ANSI LIGHT OUTPUT	ANSI RUNTIME	APPROVALS
1910	1 AAA Alkaline	1.4 oz. (0.04 kg)	3.6" (9.1 cm)	39	1h	N/A
1920	2 AAA Alkaline	2.2 oz. (0.06 kg)	5.3" (13.5 cm)	67	2h 45m	N/A
2000	3 C Alkaline	12.8 oz. (0.36 kg)	7.79" (19.8 cm)	53	5h	CI D2
2010 LED	3 C Alkaline	13.4 oz. (0.38 kg)	8.11" (20.6 cm)	109	32h	CI II III D1
2220 LED	2 CR2032 Lithium*	1 oz. (0.03 kg)	3.5" (8.9 cm)	9	34h	CI D1
2370	2 AA Alkaline	6.5 oz. (0.18 kg)	6.43" (16.3 cm)	100 (high) 13 (low)	3h 45m (high) 41h 15m (low)	N/A
2380	2 AA Alkaline	6.6 oz. (0.19 kg)	6.44" (16.4 cm)	154 (high) 23 (low)	13h (high) 13h (low)	N/A
2400	4 AA Alkaline*	7.1 oz. (0.2 kg)	6.49" (16.5 cm)	45	3h 45m	CI D1
2410 LED	4 AA Alkaline*	7.3 oz. (0.21 kg)	7" (17.8 cm)	126	7h 15m	CI II III D1
3315	3 AA Alkaline*	6.2 oz. (0.18 kg)	6.14" (15.6 cm)	113	9h 45m	CI D1
3715	4 AA Alkaline (not included)	14.4 oz. (0.41 kg)	5.36" (16.6 cm)	154 (high) 23 (low) Downcast 32 Flashing 142	4h 45m (high) 8h 30 (low) Downcast 31h Flashing 10h	CI D1
9410 L	7.4V, 6.6Ahr. Lithium-Ion (included)	49.28 oz. (1.4 kg)	8.75" (22.2 cm)	1131 (high), 558 (low)	3h 45m (high), 9h (low)	N/A

CASES	INTERIOR DIMENSIONS		EXTERIOR DIMENSIONS	
	inches	centimeters	inches	centimeters
iM2075	9.50" x 7.50" x 7.25"	(24.1 x 19 x 18.4 cm)	11.80" x 9.80" x 7.70"	(30 x 24.9 x 19.6 cm)
iM2370	18.20" x 12.10" x 5.20"	(46.2 x 30.7 x 13.2 cm)	20.00" x 14.70" x 5.80"	(50.8 x 37.3 x 14.7 cm)
0450 Tool Chest	20.56" x 10.97" x 12.65"	(52.2 x 27.9 x 32.1 cm)	23.95" x 14.75" x 17.95"	(60.8 x 37.5 x 45.6 cm)
1510M	19.75" x 11.00" x 7.60"	(50.1 x 27.9 x 19.3 cm)	23.55" x 14.36" x 10.62"	(59.8 x 36.5 x 27 cm)
1600	21.43" x 16.50" x 7.87"	(54.4 x 41.9 x 20 cm)	24.25" x 19.43" x 8.68"	(61.6 x 49.3 x 22 cm)
1770	54.58" x 15.58" x 8.63"	(138.6 x 39.6 x 21.9 cm)	57.42" x 18.48" x 11.23"	(145.8 x 46.9 x 28.5 cm)