











**PELICAN™ RALS
SPECIFICATIONS**

**REMOTE AREA LIGHTING SYSTEMS (RALS)
PORTABLE LED WORKLIGHT SOLUTIONS**

MODEL	9430	9430SL	9440	9455	9460/M
Light Source	High Flux LEDs	High Flux LEDs	High Flux LEDs	High Flux LEDs	High Flux LEDs
Lamp Heads	1	1	1	1	2
No. of LEDs	6	24	12	10	10 (per head)
Beam Spread	125°	10°	125°	125°	120°
Power Source	12v Rechargeable, Sealed	12v Rechargeable, Sealed	Rechargeable Lithium ion	Rechargeable NiMH	12v Rechargeable, Sealed
Calculated Lumen Value	1500 (Low) 3000 (High)	1000 (Low) 2000 (High)	5300 (Variable)	800 (Low) 1600 (High)	12,000 (Variable)
Battery Run Time	15h (Low) 8h (High)	15h (Low) 8h (High)	8h (Low), 4h (Medium) 1h 30m (High)	10h (Low) 5h (High)	24h (Low) 3h (High)
Dimensions Closed (L x W x D)	15.75" x 7.87" x 9.06" (40 x 20 x 23 cm)	15.75" x 7.87" x 9.06" (40 x 20 x 23 cm)	37.40" x 7.87" x 0" (95 x 20 x 0 cm)	15.35" x 7.87" x 9.06" (39 x 20 x 23 cm)	23.25" x 14.00" x 9.25" (59.1 x 35.6 x 23.5 cm)
Mast Ext. Height	32.28" (82 cm)	32.28" (82 cm)	85.0" (215.8 cm)	31.50" (80 cm)	79.50" (201.9 cm)
Weight	22.65 lbs. (10.27 kg)	22.05 lbs. (10 kg)	16.09 lbs. (7.3 kg)	16 lbs. (7.2 kg)	64 lbs. (29 kg)
Colors					

Safety Certification: CI, D1

MODEL	9470/M	9480	9490	9500	9600
Light Source	High Flux LEDs	High Flux LEDs	High Flux LEDs	High Flux LEDs	High Flux LEDs
Lamp Heads	4	1	1	3	1
No. of LEDs	10 (per head)	8	10	24 white 12 red (per head)	14
Beam Spread	120°	125°	125°	210° Diffused	125°
Power Source	12v Rechargeable, Sealed	12v Rechargeable, Sealed Lead Acid SLA	12v Rechargeable, Sealed Lead Acid SLA	110V AC	110V AC
Calculated Lumen Value	24,000 (Variable)	1000 (Low) 3000 (Medium) 4000 (High)	6000 (Variable)	1200 (red LED) 6000 (white LED)	3000
Battery Run Time	24h. (Low) 2h 45m (High)	28h (Low) 8h (Medium) 6h (High)	24h (Low) 12h (Medium) 3h 30m (High)	AC Powered	AC Powered
Dimensions Closed (L x W x D)	24.75" x 20.00" x 11.75" (62.9 x 50.8 x 29.8 cm)	15.50" x 6.50" x 10.25" (39.4 x 16.5 x 26 cm)	20.00" x 6.50" x 11.25" (50.8 x 16.5 x 28.6 cm)	20.62" x 16.87" x 8.12" (52.4 x 42.8 x 20.6 cm)	18.31" x 8.27" x 4.72" (46.5 x 21 x 12 cm)
Mast Ext. Height	82.00" (208.3 cm)	23.75" (60.3 cm)	72.0" (182.8 cm)	N/A	114.00" (289.6 cm)
Weight	108 lbs. (47.17 kg)	27.5 lbs. (12.47 kg)	32.0 lbs. (14.51 kg)	29.8 lbs. (13.5 kg)	9.04 lbs. (4.1 kg)
Colors					

ACCESSORIES

MODEL	9430	9430SL	9440	9455	9460/M
Accessory	<ul style="list-style-type: none">• 9436B - 12/24V Vehicle Charger• 9437B - Extension Cord (Black Connector) 118 inches (3m)• 9430TP - Tripod• 1460AALG Case with custom fit foam	<ul style="list-style-type: none">• 9436 - 12/24V Vehicle Charger• 9437 - Gen I Extension Cord (Blue Connector) 118 inches (3m)• 9430TP - Tripod• 1460AALG Case with custom fit foam	<ul style="list-style-type: none">• 9447 12/24v Vehicle Charger	<ul style="list-style-type: none">• 1460AALG Case with custom fit foam	N/A

MODEL	9470/M	9480	9490	9500	9600
Accessory	N/A	<ul style="list-style-type: none">• 9487 - Padded Shoulder Strap• 9489 - Powerpack• 9447 - 12/24v Vehicle Charger		N/A	<ul style="list-style-type: none">• 9605 - Pole• 9606 - Cable (14m)• 9607 - Base



U.S.A.

CALIFORNIA
23215 Early Avenue
Torrance, CA 90505
Tel: 310.326.4700
800.473.5422
Fax: 310.326.3311
www.pelican.com

MASSACHUSETTS
147 North Main Street
South Deerfield, MA 01373
Tel: 800.542.7344
Tel: 413.665.8330
www.pelican.com

**EUROPE, MIDDLE EAST
AND AFRICA**

Peli Products, S.L.U.
c/ Provença, 388, Planta 7
08025 · Barcelona, Spain
Tel: +34 934 674 999
Fax: +34 934 877 393
www.peli.com

JAPAN

Pelican Products K.K.
Nisso 22 Bldg 9F
1-11-10 Azabu Dai
Minato ward Tokyo
106-0041 Japan
Tel: +81 33 585 9100
Fax: +81 33 585 9109
www.pelican.com/jp

INTERNATIONAL

CANADA
Pelican Products ULC
10221-184th Street
Edmonton, Alberta
T5S 2J4 Canada
Tel: +780 481 6076
Fax: +780 481 9586
www.pelican.com/ca

AUSTRALIA
Pelican Products Pty Ltd
West Wing, Platinum Building,
Suite 2.33, 4 Ilya Av
Erina NSW 2250
Tel: +612 4367 7022
Tel: +612 4367 7066
www.pelicanaustralia.com

CHINA
Pelican Products China Representative Office
Pine City Building, Room 1026
777 Zhaojiabang Road
Shanghai, China 200032
Tel: +86 21 64189685
Tel: +86 21 64189679
Fax: +86 21 64189679
www.pelican.com/cn

**INDIA and SOUTH ASIA
(Bangladesh, Bhutan, Maldives, Nepal, Sri Lanka)**

Pelican Products and Services India Pvt. Ltd
GF 9&10, Augusta Point, Sector-53, Golf Course Road,
Haryana, Gurgaon 122002
Tel: +91 124 4377227 • Fax: +91 124 4049227
www.pelican.com

**SE ASIA and rest of ASIA
(Hong Kong, Macau, Taiwan, Pakistan)**

No.777, Pine City Building ZhaoJiaBang Road
#10-26 XuHui District
Shanghai, China 200032
Toll Free: +1 800-820-3082
Tel: +86 21 64189685
Fax: +86 21 64189679
www.pelican.com

LATIN AMERICA

23215 Early Avenue
Torrance, California 90505 USA
Tel: +1 310-326-4700 x1462
Fax: +1 310-325-5740
www.pelican.com

Pelican Products, Inc.
23215 Early Avenue, Torrance, CA 90505
Tel (310) 326-4700 • Toll Free (800) 473-5422 • Fax (310) 326-3311
0030-000-700 JN/22

PELICAN.COM

DESIGNED IN

USA

All trademarks are registered and/or unregistered trademarks of Pelican Products, Inc., its subsidiaries and/or affiliates. See pelican.com/warranty for full details.

For warranty details go to www.pelican.com/warranty

**REMOTE AREA
LIGHTING SYSTEMS (RALS)**

FULL LINE BROCHURE



SINCE 1976



REMOTE AREA LIGHTING SYSTEMS (RALS)
PORTABLE LED WORKLIGHT SOLUTIONS



Providing increased performance, safer working conditions, emergency preparedness and greater flexibility, Pelican's RALS line is the modern alternative to generator based lighting:

- Silent performance
- No flammable fuel
- Eliminated trip hazards
- No exhaust fumes
- Remote activation
- Low heat signature



CI, D1

Mobility Kit

Mobility Kit

9600 Pole, Base & Cable (not shown)
Sold Separately

9500 includes:
• 3 LED light heads,
• (3) 12' connector cables
• Hanging straps
• AC power adapter in a Pelican™ Protector Case™.

9430	9430SL	9455	9480	9490	9440	9460	9460M	9470	9470M	9500	9600
- Up To 3,000 Lumens - Wide 125° Beam - Large Area Coverage	- Up To 2,000 Lumens - Focused 10° Spot Beam - 200 Yard Reach	- Up To 1,600 Lumens - CI, D1 Safety Certified	- Up To 4,000 Lumens - Three Preset Light Levels - Full Time Battery Level Indication	- Up To 6,000 Lumens - Deployable 6' Mast - Intelligent Control System - Full Time Battery Level Indication	- Up To 5,300 Lumens - Deployable 7' Mast - 125 Degree Beam Spread	- Up To 12,000 Lumens - Telescoping Dual LED Light Heads - 12 volt Power Supply Port w/ USB - Housed in a Pelican™ Protector Case™	- Up To 12,000 Lumens - Multi-Terrain Trolley - 12 volt Power Supply Port w/ USB - Housed in a Pelican™ Protector Case™	- Up To 24,000 Lumens - Four Telescoping LED Light Heads - 12 volt Power Supply Port w/ USB - Housed in a Pelican™ Protector Case™	- Up To 24,000 Lumens - Multi-Terrain Trolley - 12 volt Power Supply Port w/ USB - Housed in a Pelican™ Protector Case™	- Up To 6,000 Lumens - Shelter Lighting System - White/Red LEDs in Each Head - Daisy-Chain Up To 3 Light Heads - Housed in a Pelican™ Protector Case™	- 3,000 Lumens Per Light Head - Adjustable Light Beam - Stackable - Daisy-Chain Multiple Light Heads - AC Powered